




PRODUCT LINE-UP & SPECIFICATION

Series		SuperGD+ series		
Picture				
Product Number		SP-750GD	SP-850GD	SP-1050GD
Model Number		HP1-F750GD-F14C	HP1-F850GD-F14C	HP1-H1050GD-F14C
Input	Voltage	100-240V~	100-240V~	100-240V~
	Current	10A	10A	15-8A
	Total Watts	750W	850W	1050W
Output	+5V	22A	22A	22A
	+3.3V	22A	22A	22A
	+12V1	62.5A	70.9A	87.5A
	+12V2	-	-	-
	+12V3	-	-	-
	+12V4	-	-	-
	-12V	0.3A	0.3A	0.3A
	+5Vsb	3A	3A	3A
	+5V+3.3V	120W	120W	120W
	+12V Combined	750W	850W	1050W
Connectors	24Pin / *20+4Pin	*1	*1	*1
	CPU 4Pin	0	0	0
	CPU 4+4Pin	2	2	2
	CPU 8Pin	0	0	0
	PCI-E 6+2Pin	4	6	8
	PCI-E 6Pin	0	0	0
	S-ATA	9	9	9
	HDD	4	4	4
	FDD	1	1	1
Dimension (W/D/H)(mm)		150x160x86	150x160x86	150x160x86
Fan Bearing		2-Ball	2-Ball	2-Ball
Fan Size(cm)		13.5cm	13.5cm	13.5cm
Modular Cable		Fully modular	Fully modular	Fully modular
Off-delay Fan		V	V	V
Dc to Dc		V	V	V
LLC		V	V	V
Japan Capacitors		V	V	V
Solid-state Capacitors		V	V	V
Double-sided PCB		V	V	V
+12V Rail		1 Rail	1 Rail	1 Rail
Protection		UVP/OVP/ OPP/SCP/OC/OTP	UVP/OVP/ OPP/SCP/OC/OTP	UVP/OVP/ OPP/SCP/OC/OTP
Safety		CE / CB / TUV / cTUVus / FCC	CE / CB / TUV / cTUVus / FCC	CE / CB / TUV / cTUVus / FCC
80 PLUS		